

METHOD FOR GRAPHICALLY REPRESENTING
AND/OR PROCESSING VALUES OF DATA TYPESFIELD OF THE INVENTION

The present invention relates to a method for graphically
representing and/or processing values of data types of a
formally defined data structure existing as a value tree.

BACKGROUND INFORMATION

Programming and description languages may require a formal
syntax to describe data types and their values. Methods are
believed to be available for defining data structures using a
formal notation, independently of a specific language. The
data types defined in accordance with one of these methods may
be of a desired complexity and may dynamically change in part.
Thus, such data types should be clearly represented for
display purposes or to enable user input of values. This
should be done for the management of communications networks,
since very complex data structures may be processed in these
networks.

In various languages and syntax notations, rules exist for
textually representing values. Thus, for example, when working
with ASN.1 data types in accordance with ITU-T recommendation
X.208, the value is represented as a character string in a
manner, which is not believed to be very straightforward.

It is believed that the structure of the data type may be
recognizable when the form of representation of a tree is
used. A representation of this kind is discussed in the
reference "IBM TMN Development Platform", Piscataway, New
Jersey, U.S.A., 1998. Another method is believed to include
assigning the value of an attribute to a graphic component by
manually creating rules, for example, defining the color of

SUBSTITUTE SPECIFICATION

the graphic object by the value of the data type, discussed, for example, in the reference "Objective Systems Integrators: NetExpert Framework Overview", Folsom, California, U.S.A., 1997.

5

Since any data type definitions at all may be possible, it is believed that the available methods may expend a great deal of time programming a separate graphical user-interface window for each new data type.

10

SUMMARY OF THE INVENTION

An exemplary embodiment and/or exemplary method of the present invention is directed to reducing the time expenditure on programming and to achieve a straightforward and clear representation, which will enable the data structure to be tested and, if desired, processed.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing that:

- a window may be assigned as a graphical user interface to the data structure;
- generic, scalable, graphical user-interface components may be inserted hierarchically in the window, the value tree of the data structure being mapped onto the user-interface components;
- the graphical user interface components may be in a relation to the nodes of the value tree in a manner that is recognizable to the user; and
- a graphical or textual representation of the value may be selectable for each subtree of the value tree.

The clear, straightforward representation of a complex data type using the exemplary method in accordance with the present invention may save the user from having to search extensively for definitions and may help to avoid errors when inputting values for this data type. In this context, the exemplary

method of present invention may provide the concealing of
redundant information and the presenting of information in
detail, since an exemplary embodiment and/or exemplary method
of the present invention is directed to providing that each
5 user has a chance to decide which information should be
displayed and for which information a compact representation
suffices. Another exemplary embodiment and/or exemplary method
of the present invention is directed to providing a simple
value assignment to be made in the processing of the data
10 types.

Another exemplary embodiment and/or exemplary method of the
present invention is directed to providing for a simple and
secure value assignment to be carried out in that, for a
15 processing of the value tree, a list of all values which are
compatible with respect to assignment with the represented
data type may be derived for each node, and that, in each
case, one value may be selected from the list for a value
assignment. To avoid input errors, it may be provided when
20 compiling value lists, that the number of values to be
accepted in the list are restricted in accordance with
predefined rules, depending on the current context.

Another exemplary embodiment and/or exemplary method of the
25 present invention is directed to providing for a visualization
of the window to be first undertaken at the time of an
initialization of the graphical user interface and, after
that, data, for example, value lists, to be initialized, which
may be derived for a processing. As a result of the faster
30 display build-up associated therewith, the user may already
obtain an overview of the data structure before all data
required for displaying and processing the data type are
initialized.

35 Another exemplary embodiment and/or exemplary method of the
present invention is directed to providing that a data type

may be graphically displayed when no additional information, described as metadata, on the data type is available in the graphical interface application, when the value to be represented is transferred in a transfer syntax, which contains all necessary information for the representation with respect to the data type and the value assignment.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing data types, whose exact type assignment may first be determined at the execution time in accordance with the late binding principle, and inserted as a dynamically changeable subtree in the value tree represented by the graphical user interface. From this, an advantage for these data types may be that the representation of the current value assignment does not first require opening subwindows (or subforms), but may take place directly in the main window.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing that for data types whose exact type assignment may be first defined in accordance with the late binding principle at the execution time by the marking of another node (for example, "ANY DEFINED BY" in the description language ASN.1), the user may be prompted to input whether the assignment should be carried out automatically or following a manual input. Thus, an assignment may occur when the information required for the automatic assignment is not available.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing that values may be transferred from one subtree into another by intermediately storing and clicking on the subtree in question. In the process, an assignment compatibility of the data types may be assigned to the subtrees. However, it may not be necessary for the data types to be instantiated within the same value tree.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing a simple use, together with other programs, and the simple mapping of the overall identity in that the exemplary method may be implemented by one or more program modules that may be integrated in the application programs.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing that additional information to be displayed may be stored for each node of the value tree which may be uniquely named by the displayed type and the relation to the higher-order type. In this manner, additional text elements may be displayed for specific data types, which may be produced at any point in time following the program creation, and which may be dynamically integrated in the interface at the execution time.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing continual checking during inputting of a value to determine whether the input value is permissible for the corresponding data type, and whether the input value is identical to the currently active value of the data type, and that the result be made known to the user. Another exemplary embodiment and/or exemplary method of the present invention is directed to further enhancing security and the speed attained in the processing of data types.

Another exemplary embodiment and/or exemplary method of the present invention is directed to providing that the display and/or the processing may be facilitated in that the display format may be altered already at the time that a value is input and, thus, for example, a numerical value may be either displayed as a decimal or binary value, before a value is accepted into the value tree.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a window of a graphical user interface according to an exemplary embodiment and/or exemplary method of the present invention.

Figure 2 shows a formal data definition in accordance with ASN.1.

Figure 3 shows the principle of a generic, graphic representation.

DETAILED DESCRIPTION

Figure 1 shows the relevant graphical user interface as a window 1, in which all included data types are contained as graphical user-interface components. The root of the value tree (Figure 3) is indicated by the GetArgument SEQUENCE. Input bars 2, 3 and 4, having the labels "globalForm", "localForm" and "baseManagedObjectInstance" correspond to the leaf objects of the value or GUI tree. Buttons 5 through 9 can be used to select between a textual representation (minus) and a graphic representation (plus) for each node and each leaf object.

Other buttons 10, 11 (radio buttons) may be used to select between two data types to be alternatively processed (in this case, leaf objects). Input bars 2, 3, 4 are each provided with a button 12, 13, 14, which can be used to open a window 15 for selecting values stored as constants.

In addition, the graphical user interface has buttons 16, 17 for terminating the processing and storing the processed data, as well as for exiting the graphical user interface without storing the data.

Figure 2 shows the definitions of the data types "GetArgument" and "BaseManagedObjectClass" in the form of a structured text.

The type "GetArgument" includes two components,
"baseManagedObjectClass" and "baseManagedObjectInstance", the
names being given to the left, and the types of the components
to the right, namely "BaseManagedObjectClass" and
5 GraphicString". The type "BaseManagedObjectClass" is a CHOICE
having likewise two components, namely "globalForm" of type
"OBJECTIDENTIFIER" and "localForm" of type "INTEGER".

10 Figure 3 shows the principle of a generic, graphic
representation of the formal data definition illustrated in
Figure 2. In this context, the value tree is shown to the
left, while the graphic representation is indicated to the
right. In this instance and in the text that follows, the
abbreviation GUI (= Graphical User Interface) is also used for
15 the graphical user interface. Solid lines running between the
blocks signify that the underlying or subjacent elements are
contained in the node situated above them, while the dotted
lines signify that each graphic representation is in relation
to the particular data type.
20